

K-INLINE-DRG AG IG O SEKUNDAERENTLU

Inline pressure regulators, non-self-relieving

HANSA FLEX

Eigenschappen

| | |
|--------------------|-----------------------------|
| Werkdruk | max. 18 bar |
| Temperatuurgebied | 0 °C to +60 °C |
| Tolerantie druk | ± 0.3 bar at 10 l/min |
| Behuizing | Zinc |
| overige onderdelen | Brass, NBR, stainless steel |



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

This single-acting diaphragm regulator can be installed in any pneumatic system. Since the pressure is preset in the factory and cannot be altered, the product is also tamper-proof. We recommend mounting the regulator directly on the tool to make sure the correct pressure is applied. In this case, the tool is never stressed by the higher pressure of the supply system and is protected against pressure fluctuations in hoses, pipes, etc. Energy efficiency and economic efficiency can be achieved by using an inline pressure regulator.

Artikel

| Aanduiding | Schroefdraad | Werkdruk vooringesteld | A (mm) | B | SW (mm) |
|----------------|--------------|------------------------|-----------|---------|------------|
| K- 07 25 02 75 | G 1/4 | 1 bar | 34,0 | 52,0 mm | 17 |
| K- 07 25 02 76 | G 1/4 | 2 bar | 34,0 | 52,0 mm | 17 |
| K- 07 25 02 77 | G 1/4 | 3 bar | 34,0 | 52,0 mm | 17 |
| K- 07 25 02 78 | G 1/4 | 4 bar | 34,0 | 52,0 mm | 17 |
| K- 07 25 02 79 | G 1/4 | 5 bar | 34,0 | 52,0 mm | 17 |
| K- 07 25 02 80 | G 1/4 | 6 bar | 34,0 | 52,0 mm | 17 |
| K- 07 25 02 81 | G 1/4 | 6,5 bar | 34,0 | 52,0 mm | 17 |
| K- 07 25 02 82 | G 1/4 | 7 bar | 34,0 | 52,0 mm | 17 |