

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Eigenschappen

Bedrijfstemperatuur	-60 °C to +100 °C (PA 12)
Eigenschappen	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Buislengte	3 m
Verpakkingseenheid	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Materiaal	Polyamid PA 12, hard (according to DIN 73378)



Aanwijzing

Operating pressure with 2.5 x overpressure safety!

Andere gegevens op aanvraag.

Beschrijving

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Artikel

Aanduiding	Uitw. Ø buis (mm)	Buis-binnen-Ø (mm)	max. bedrijfsdruk bij 20°C (bar)	Kleur
K- 07 10 04 56	12	9	38	blauw
K- 07 10 04 58	12	9	38	Zwart
K- 07 10 04 60	15	12	25	blauw
K- 07 10 04 62	15	12	25	Zwart
K- 07 10 04 64	18	14	28	blauw
K- 07 10 04 66	18	14	28	Zwart
K- 07 10 04 68	22	18	22	blauw
K- 07 10 04 70	22	18	22	Zwart
K- 07 10 04 72	28	23	20	blauw
K- 07 10 04 74	28	23	20	Zwart