

# K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

**HANSA FLEX**

## Eigenschappen

<b>Bedrijfstemperatuur</b>	-60 °C to +100 °C (PA 12)
<b>Eigenschappen</b>	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
<b>Buislengte</b>	3 m
<b>Verpakkingseenheid</b>	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
<b>Materiaal</b>	Polyamid PA 12, hard (according to DIN 73378)



## Aanwijzing

Operating pressure with 2.5 x overpressure safety!

Andere gegevens op aanvraag.

## Beschrijving

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Artikel

Aanduiding	Uitw. Ø buis (mm)	Buis-binnen-Ø (mm)	max. bedrijfsdruk bij 20°C (bar)	Kleur
K- 07 10 04 56	12	9	38	blauw
K- 07 10 04 58	12	9	38	Zwart
K- 07 10 04 60	15	12	25	blauw
K- 07 10 04 62	15	12	25	Zwart
K- 07 10 04 64	18	14	28	blauw
K- 07 10 04 66	18	14	28	Zwart
K- 07 10 04 68	22	18	22	blauw
K- 07 10 04 70	22	18	22	Zwart
K- 07 10 04 72	28	23	20	blauw
K- 07 10 04 74	28	23	20	Zwart