K-HRF HEBELSTECKER

Handheld tyre gauges with tyre valve connector



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

Single-lever operation: Inflation, deflation and checking with a single handle. To check - lever in home position. To deflate - lever actuated half-way. To inflate - lever fully actuated. High-quality, concentric pressure gauge 80 mm Ø. Available for the following measuring ranges: 0 to 4 bar/50 psi, 0 to 10 bar/140 psi, 0 to 25 bar/350 psi. These pressure gauges are effectively protected against shock and impact by means of a free-standing plastic cap. They can be loaded against gauge pressure and up to the maximum scale value. With push-in plug for DN 7.2 coupling.

Artikel

Aanduiding	Meetbereik	Aanwijzing
K- 07 10 04 10	0 bis 4 bar/56 psi	Calibrated
K- 07 10 04 11	0 bis 4 bar/56 psi	Uncalibrated
K- 07 10 04 12	0 bis 12 bar/170 psi	Calibrated
K- 07 10 04 13	0 bis 12 bar/170 psi	Uncalibrated
K- 07 10 04 14	0 bis 25 bar/350 psi	Uncalibrated

Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.