

K-SPIR SCHL

Spiral hose, without fittings

Eigenschappen

Toepassing Air, gases, oils, greases, fuels, organic and inorganic substances

Bedrijfstemperatuur -40 °C to +100 °C



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Artikel

Aanduiding	Ø slang binnen (mm)	Ø slang buiten (mm)	Ø spiraal buiten (mm)	Wikkelingen	Max. working pressure resistance at 23°C (bar)	max. werklengte (m)
K- 07 10 07 51	3,1	4,7	38	144	22	10,0
K- 07 10 07 52	4,8	6,3	75	140	16	22,5
K- 07 10 07 53	6,3	7,9	75	135	13	22,5
K- 07 10 07 49	7,9	9,5	115	90	12	22,5
K- 07 10 07 50	9,5	11,8	140	70	11	22,5

Toebehoren

K-DREHBARE VERSCHR KNICK Swivel adapters with kink protector

K-STARRE VERSCHRAUBUNG Rigid adapters with kink protector