

K-HYDR-KUPPLUNG IG POM

Hydraulic couplings, POM

HANSA FLEX

Eigenschappen

Werkdruk	See table. All values referred to a medium temperature of 50 °C (static working pressure)
Debiet lucht	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
Mediumtemperatuur	-20 °C to +90 °C
Behuizing, huls	POM (Delrin), white
Ventiel	Stainless steel 1.4305
Veer, snapring, kogels	stain less steel
Afdichtmateriaal	NBR



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Artikel

Aanduiding	Aansluiting	Werkdruk (bar)	Lengte (mm)	NW	SW (mm)
K- 07 35 03 76	G 1/8 female	15,0	48,5	4,3	14
K- 07 35 03 77	G 1/4 female	15,0	57,6	6,0	19
K- 07 35 03 78	G 3/8 female	15,0	64,2	7,5	22
K- 07 35 03 79	G 1/2 female	10,0	76,0	11,0	27
K- 07 35 03 80	G 3/4 female	10,0	96,0	13,0	34