K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

Eigenschappen

Werkdruk	0 - 35 bar, maximum static working pressure (non-pulsating)
Debiet lucht	560 l/min (at 6 bar and Δp = 0.5 bar)
Mediumtemperatuur	-20 °C to +100 °C
Ontgrendelingshuls	Anodised aluminium
Veer, snapring, kogels	stain less steel
Afdichtmateriaal	NBR



Aanwijzing

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Andere gegevens op aanvraag.

Beschrijving

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artikel

Aanduiding	Aansluiting	Kleur	Lengte (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	groen	45,0	14
K- 07 35 06 81	G 1/4 male	groen	47,0	17
K- 07 35 06 82	G 1/8 female	groen	45,0	14
K- 07 35 06 83	G 1/4 female	groen	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	blauw	45,0	14
K- 07 35 06 89	G 1/4 male	blauw	47,0	17
K- 07 35 06 90	G 1/8 female	blauw	45,0	14
K- 07 35 06 91	G 1/4 female	blauw	47,0	17
K- 07 35 06 92	G 1/8 male	rood	45,0	14
K- 07 35 06 93	G 1/4 male	rood	47,0	17
K- 07 35 06 94	G 1/8 female	rood	45,0	14
K- 07 35 06 95	G 1/4 female	rood	47,0	17

Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.