K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

Eigenschappen

Werkdruk	0 - 35 bar, maximum static working pressure (non-pulsating)
Debiet lucht	1.800 l/min (at 6 bar and Δp = 0.5 bar)
Mediumtemperatuur	-20 °C to +100 °C
Behuizing	Brass
Ventiel	Die-cast zinc, nickel-plated
Ontgrendelingshuls	Anodised aluminium
Veer, snapring, kogels	stain less steel
Afdichtmateriaal	NBR



Aanwijzing

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Andere gegevens op aanvraag.

Beschrijving

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artikel

Aanduiding	Aansluiting	Kleur	Lengte (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	groen	57,5	19
K- 07 35 08 02	G 3/8 male	groen	57,5	19
K- 07 35 08 03	G 1/4 female	groen	55,5	19
K- 07 35 08 04	G 3/8 female	groen	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	blauw	57,5	19
K- 07 35 08 10	G 3/8 male	blauw	57,5	19
K- 07 35 08 11	G 1/4 female	blauw	55,5	19
K- 07 35 08 12	G 3/8 female	blauw	54,5	19
K- 07 35 08 13	G 1/4 male	rood	57,5	19
K- 07 35 08 14	G 3/8 male	rood	57,5	19
K- 07 35 08 15	G 1/4 female	rood	55,5	19
K- 07 35 08 16	G 3/8 female	rood	54,5	19

Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.