
K-INLINE-EJEKTTOREN VR

Inline ejectors »VR«, screw connection

Eigenschappen

Eigenschappen	Vacuum generator with high maximum vacuum level (85% vacuum) No moving parts, which means no wear and no maintenance ultra small footprint, suitable for confined spaces minimal air consumption \nlow noise
Toepassing	by screwing / plugging into the distribution beam direct attachment to the suction pad for handling various workpieces
Behuizing	Aluminium eloxed (type VR)
Spuitmondensysteem	Brass (type VR)
Aansluiting	Steekaansluiting





Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Artikel

Aanduiding	Spuitmondgrootte	Afzuigaansluiting	Persluchtaansluiting	Vacuümaansluiting	Evacuatiegraad	Luchtverbruik zuigen (L/min)	max. zuigvermogen (L/min)	Lengte (mm)	Werkdruk (bar)
K- 07 45 01 29	0,7	M 5 male	G 1/4 IG	G1/8 female	90 %	21,0	14,0	35,0	5,0
K- 07 45 01 30	0,9	M 5 male	G 1/4 IG	G1/8 female	89 %	36,0	21,0	35,0	5,0

Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.