

K-DRUCKSCHALTER VAKUUM

Combined vacuum/pressure switch

HANSA FLEX

Eigenschappen

| | |
|--------------------------------|---|
| Constructie | PNP |
| Aansluiting meetmedium | G 1/8 male and M 5 female |
| Hysterese | Adjustable: 3 to 25% of set value |
| Temperatuurgebied | 0 - 50 °C |
| Middelen | Non-aggressive gases. dry, oil-free air |
| Behuizing | Polycarbonate |
| Uitgangssignaal | Analogue: 1 to 5 V |
| Elektrische aansluiting | Male connector M8, four pin |
| Schakelvermogen | 125 mA |
| Stroomverbruik | 30 mA |
| Toestandsindicatie | LED |



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

Universal electronic vacuum and pressure switch for safety monitoring, optimisation of cycle times and regulation circuits. Its small size and low weight permit installation directly at the point of use. Suitable for all special applications in the vacuum and compressed air sectors. Adjustable vacuum limit value and continuous vacuum monitoring.

Artikel

| Aanduiding | G1 buiten | G2 binnen | G3 buiten | L (mm) | L1 (mm) | Meetbereik | Spanning |
|----------------|-----------|-----------|-----------|-----------|------------|----------------|----------------|
| K- 07 45 01 31 | G 1/8 | M 5 | M 8 x 1 | 44,0 | 62,0 | -1 bis +10 bar | 10.8 - 30 V DC |