

K-DRS MDR 5 M ENTLASTU VENT

»MDR 5« pressure switches, with unloading valve / on/off switch / flange 1/4, without motor protection circuit

HANSA FLEX

Eigenschappen

| | |
|------------------------|------------------------------------|
| Mediumtemperatuur | -5 °C to +80 °C |
| max. uitschakeldruk | 16 bar |
| Schakelvermogen | 5,5 kW |
| Contactsoort | NC (3-pole) |
| max. schakelfrequentie | 120 (electrical), 600 (mechanical) |
| Beschermingsklasse | IP 54 |



Aanwijzing

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Andere gegevens op aanvraag.

Beschrijving

Three-phase version

Bestelaanwijzingen

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Extra informatie

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Artikel

| Aanduiding | Persluchtaansluiting | Instelbereik |
|----------------|----------------------|----------------|
| K- 07 30 24 25 | G 1/2 | 2,0 - 11,0 bar |
| K- 07 30 24 27 | G 1/2 | 2,5 - 16,0 bar |