


K-T-STUECKE IG 1 2

Tees, female-female-female

HANSA FLEX

Eigenschappen

| | |
|---------------------|------------------------------|
| Werkdruk | 60 bar |
| Bedrijfstemperatuur | Max. 150 °C |
| Schroefdraad binnen | Parallel to DIN EN ISO 228-1 |
| Materiaal | messing vernikkeld |



Aanwijzing

Andere gegevens op aanvraag.

Artikel

| Aanduiding | Schroefdraad | L1 (mm) | L2 (mm) | SW |
|----------------|--------------|------------|------------|-------|
| K- 07 40 48 92 | M 5 | 22,0 | 11,0 | 9 mm |
| K- 07 40 11 04 | G 1/8 | 42,0 | 21,0 | 10 mm |
| K- 07 40 11 05 | G 1/4 | 51,0 | 25,5 | 13 mm |
| K- 07 40 11 06 | G 3/8 | 56,0 | 28,0 | 17 mm |
| K- 07 40 11 07 | G 1/2 | 67,0 | 33,5 | 21 mm |
| K- 07 40 11 14 | G 3/4 | 73,0 | 36,5 | 25 mm |
| K- 07 40 11 15 | G 1 | 90,0 | 45,0 | 30 mm |