


# K-W90 GAM IG

Female elbows with female G thread

**HANSA FLEX**

## Eigenschappen

|                    |   |
|--------------------|---|
| Werkdruk           | Dependent on operating temperature; Max. 10 bar (at 20 °C); Max. 1 bar (at 60 °C) |
| Vastschroefelement | Polyamide (PA)  |
| Klemring           | Polypropylene (PP)  |
| Moer               | Polypropylene (PP)  |



## Aanwijzing

Andere gegevens op aanvraag.

## Beschrijving

Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. <br>Not suitable for use with acids.

## Artikel

| Aanduiding     | Schroefdraad | voor slang   | L1<br>(mm) | L2<br>(mm) |
|----------------|--------------|--------------|------------|------------|
| K- 07 40 32 98 | G 1/8        | 4 mm / 6 mm  | 26,0       | 17,0       |
| K- 07 40 32 99 | G 1/8        | 6 mm / 8 mm  | 29,0       | 17,0       |
| K- 07 40 33 00 | G 1/4        | 4 mm / 6 mm  | 29,0       | 20,0       |
| K- 07 40 33 01 | G 1/4        | 6 mm / 8 mm  | 32,0       | 20,0       |
| K- 07 40 33 02 | G 1/4        | 8 mm / 10 mm | 35,0       | 20,0       |