

# K-SDR AG

Banjo elbows, parallel male thread

**HANSA FLEX**

## Eigenschappen

|                   |                    |
|-------------------|--------------------|
| max. bedrijfsdruk | 18 bar             |
| bruikbare slangen | PA, PE, PU         |
| Materiaal         | messing vernikkeld |



## Aanwijzing

Andere gegevens op aanvraag.

## Artikel

| Aanduiding     | Schroefdraad | voor slang   | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|--------------|--------------|------------|------------|-------|
| K- 07 40 33 99 | M 5          | 5 mm / 3 mm  | 17,0       | 17,5       | 8 mm  |
| K- 07 40 34 00 | M 5          | 6 mm / 4 mm  | 18,0       | 17,5       | 8 mm  |
| K- 07 40 34 04 | G 1/8        | 6 mm / 4 mm  | 24,0       | 28,0       | 14 mm |
| K- 07 40 34 05 | G 1/8        | 8 mm / 6 mm  | 24,0       | 28,0       | 14 mm |
| K- 07 40 34 02 | G 1/4        | 6 mm / 4 mm  | 26,0       | 29,5       | 17 mm |
| K- 07 40 34 03 | G 1/4        | 8 mm / 6 mm  | 26,0       | 29,5       | 17 mm |
| K- 07 40 34 01 | G 1/4        | 10 mm / 8 mm | 27,5       | 33,0       | 17 mm |
| K- 07 40 34 07 | G 3/8        | 8 mm / 6 mm  | 27,5       | 31,5       | 22 mm |
| K- 07 40 34 06 | G 3/8        | 10 mm / 8 mm | 28,5       | 31,5       | 22 mm |