K-KONDENSA DRUKODRAIM

Drain for compressed air condensate



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

Ruggedly designed, cycle-controlled drain system for controlled drainage of compressed air condensate, proven thousands of times over and ready to use immediately.
In contrast with conventional clock generators, the blowing and pause times of the »drukodrain« are not set in seconds or minutes but in bar or m3/min, depending on the pneumatic system installed upstream. Efficient and reliable operation is assured. Benefits of »drukodrain«: Clock generator settings according to compressed air system: "bar" - for operating pressure, "m3/min" - for compressor or dryer capacity, Suitable for compressor / dryer capacities up to 20 m3/min, Integrated dirt pan and G 1/2 ball valve, 2 m connection cable with plug (230 V / 50 Hz) included.

Artikel

Aanduiding	Werkdruk bar	Spanning
K- 07 25 09 23	Max. 16 bar	230 V / 50 Hz

Reserveonderdelen

K-ZUBEH KONDENSATABLEITER	Accessories for drain for compressed air condensate

Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.