

# K-FI REGL METALLBEHAE S MANO MULTIF

Filter regulators with metal bowl and sight glass, incl. pressure gauge

**HANSA FLEX**

## Eigenschappen

|                                   |   |
|-----------------------------------|---|
| Ingangsdruk                       | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)        |
| Mediumtemperatuur                 | max. 60 °C  |
| Omgevingstemperatuur              | Max. 60 °C  |
| Porienwijdte in het filterelement | 5 µm (C55: 40 µm)   |
| Afdichtmateriaal                  | NBR   |
| Veerkap                           | POM-brass   |
| Behuizing                         | Die-cast zinc, Aluminium for G 1 variant                          |
| Drain valve                       | Semi-automatic  |
| Debietwaardemeting                | At P1 = 8 bar, P2 = 6 bar and pressure drop<br>$\Delta p = 1$ bar |



## Aanwijzing

Andere gegevens op aanvraag.

## Beschrijving

Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

## Bestelaanwijzingen

Filter regulators with bowl guard and metal bowl are also available with control ranges of 0.1 - 3 bar, 0.2 - 6 bar and 0.5 - 16 bar. Please ask for more information. Lockable filter regulators available on request.

## Artikel

| Aanduiding     | Schroefdraad | Regelbereik  | Debiet (L/min) | A (mm) | B        | C (mm) | D (mm) | DN | Maat |
|----------------|--------------|--------------|----------------|--------|----------|--------|--------|----|------|
| K- 07 25 00 68 | G 1/4        | 0.5 - 10 bar | 1500           | 47,8   | 192,0 mm | 67,0   | 125,5  | 6  | 1    |
| K- 07 25 00 72 | G 3/8        | 0.5 - 10 bar | 1500           | 47,8   | 192,0 mm | 67,0   | 125,5  | 10 | 1    |
| K- 07 25 00 76 | G 1/2        | 0.5 - 10 bar | 3500           | 68,8   | 246,0 mm | 99,0   | 149,2  | 15 | 2    |
| K- 07 25 00 80 | G 3/4        | 0.5 - 10 bar | 3500           | 68,8   | 246,0 mm | 99,0   | 149,2  | 20 | 2    |
| K- 07 25 00 84 | G 1          | 0.5 - 10 bar | 12000          | 100,0  | 385,0 mm | 128,0  | 255,7  | 25 | 3    |

## Reserveonderdelen

|                                  |                           |
|----------------------------------|---------------------------|
| K-HALTERBAUSATZ                  | Holder                    |
| K-SCHALTTAFELMUTTER              | Nut                       |
| K-HALTERBAUSATZ MULTIFIX         | Holder                    |
| K-KOPPELPAKET MEHR               | Coupling packet           |
| K-KOPPELPAKET SCHMA              | Coupling packet           |
| K-METALLBEHAELTER OELER MULTIFIX | Metal tank oiler          |
| K-PC-BEHAELTER FILTER MULTIFIX   | Polycarbonate tank filter |
| K-SCHUTZKORB G                   | Protective cage           |
| K-VERSCHLEI-SATZ                 | Set of wearing parts      |
| K-FILTERELEMENT                  | Filter element            |
| K-AUTOMAT ABLASSVENTIL           | Automatic drain valve     |