

# K-SCHALTVENTILE 3/2 MULTIFIX MINI

On-off valves (3/2-way valves)

**HANSA FLEX**

## Eigenschappen

Ingangsdruk	Min. 2 bar, max. 10 bar
Mediumtemperatuur	max. 60 °C
Omgevingstemperatuur	Max. 60 °C
Elektrische aansluiting	Device plug PG 9, type B, EN 175301-803
Beschermingsklasse	IP 65 (P 54) acc. to DIN 40050
Debiet	1600 l/min
Inschakelduur relatief	100 %
Ontluchtingsaansluiting	Silencer G 1/4
Afdichtmateriaal	NBR
Behuizing	Die-cast zinc
Debietwaardemeting	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



## Aanwijzing

If several devices in the »multiflex-mini« Series are assembled together, the maximum working pressure is 12 bar.

Andere gegevens op aanvraag.

## Beschrijving

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. When they are switched off, the system is relieved at the same time.

## Artikel

Aanduiding	Schroefdraad	Magneetspoelen	A (mm)	B	C (mm)	Maat
K- 07 25 11 62	G 1/4	230 V AC, 50 Hz	45,0	29,0 mm	96,0	0
K- 07 25 11 63	G 1/4	110 V AC, 50 Hz	45,0	29,0 mm	96,0	0
K- 07 25 11 64	G 1/4	24 V DC	45,0	29,0 mm	96,0	0

## Reserveonderdelen

K-KOPPELPAKET MEHR	Coupling packet
K-GERAETESTECKER	Coupling socket
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-MAGNETSPULE MULTIFIX	Solenoid
K-SCHALLDAE SINTERBR SCHLITZ	Silencers, sintered bronze, slotted