


# K-MV O (NO) V 24 V DC H

Normally open, (NO), directly operated, 24 V DC, for high pressures

**HANSA FLEX**

## Eigenschappen

<b>Elektrische aansluiting</b>	device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket
<b>Schroefdraad beschrijving</b>	G thread acc. DIN EN ISO 228-1
<b>Mediumtemperatuur</b>	max. 80 °C when using water or oils; max. 90 °C when using with air
<b>Beschermingsklasse</b>	IP 65
<b>max. bedrijfsdruk</b>	20 bar
<b>Afdichtmateriaal</b>	FPM
<b>Behuizing, ventielzitting</b>	Stainless steel 1.4301
<b>Inwendige delen</b>	Stainless steel



## Aanwijzing

Andere gegevens op aanvraag.

## Beschrijving

Standard series in two different versions: Directly operated, Pilot-operated

## Artikel

Aanduiding	Schroefdraad	NW	A (mm)	B (mm)	C (mm)	Constructie
K- 07 30 01 46	G 1/8	1,5	70,0	40,0	76,0	2
K- 07 30 01 47	G 1/4	1,5	70,0	40,0	76,0	2
K- 07 30 01 48	G 3/8	3,0	85,0	52,0	92,0	2
K- 07 30 01 49	G 1/2	3,0	85,0	52,0	92,0	2