

K-VT 2 KUPPL 7,2 STECKNIP MS

Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8

HANSA FLEX

Eigenschappen

Werkdruk	0 - 35 bar
Mediumtemperatuur	-20 °C to +100 °C
Behuizing	Brass
Beveiliging en afdichting	Industrial glue, mid hardened



Aanwijzing

Couplings and distributors are also available separately
Andere gegevens op aanvraag.

Beschrijving

1, 2 or 3-way distributor pieces made of brass, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Extra informatie

Couplings and distributors are also available separately

Artikel

Aanduiding	Aansluiting	Koppeling	bestaande uit verdeler
K- 07 40 40 48	Plugs DN 7.2 to 7.8 / G 3/8	K-07350025	K-07404016
K- 07 40 44 27	Plugs DN 7.2 to 7.8 / G 1/2	K-07350026	K-07404017

is toebehoren bij volgende producten

K-VSEH 3-KRAFT	Receptacle combinations »3-Kraft«
K-VSEH AIRKRAFT	Receptacle combinations »airkraft«