# K-FLACHDUESE LAERMARME UN

Low-noise flat nozzles, 1/2 - 27 UNS connection

## Eigenschappen

**Materiaal** messing vernikkeld



## Aanwijzing

For noise, air consumption and blowing force values, see diagrams 1-17 in the technical information.

## Beschrijving

If correctly designed, these noise-reducing nozzles guarantee a lower noise level than conventional one-hole types with an identical blowing force. They are usually fitted with a noise-reducing plastic insert and they are recommended by the German BGIA (Institute for Occupational Safety and Health).

## Artikel

| Aanduiding | Spuitmondtypebreedte (mm) | Lengte (mm) | Materiaal | Diagram |
|---|---|---|---|---|
| **K- 07 10 09 48** | 21,5 | 100,0 | Nickel-plated brass | 11 |
| **K- 07 10 09 49** | 29,0 | 100,0 | Nickel-plated brass | 12 |
| **K- 07 10 09 50** | 21,0 | 100,0 | Nickel-plated brass | 13 |

## is toebehoren bij volgende producten

**K-H-LP TYPHOON SAFETY** High-volume blow guns »Typhoon«, without nozzle, Safety

*Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.*