K-EINGANGSPL VENTILINSEL HDM

Input plates for HDM valve terminal

Eigenschappen

Middelen	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Werkdruk	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
Regeldruk	3 - 7 bar
Temperatuurgebied	-10 °C to +60 °C
Debiet	200 Nl/min (Ø 4), 500 Nl/min (Ø 6), 800 Nl/min (Ø 8)
Aantal aansturingen	Max. 16 (e.g. 16 spring return valves)
Handmatige hulpbediening	Latching (bistable), Monostable (non-latching) version also available on request
Opgenomen vermogen	0.6 W per pilot
Beschermingsklasse	IP 65



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

These compact valve terminals, with a maximum flow rate of 800 Nl/min, can be individually adapted to the specific conditions of each application thanks tot he wide range of functions and various input and intermediate plates.Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Extra informatie

Important: The scope of supply does not include a connector. Please order separately.

Artikel

Aanduiding	Functie	Aansluiting
K- 07 15 22 49	Standard, internal pilots	Multi-pole
K- 07 15 22 48	External pilots, dual supply	Multi-pole
K- 07 15 22 54	Standard, internal pilots	With integrated Profibus DP
K- 07 15 22 53	External pilots	With integrated Profibus DP

Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.