

# K-ENDLAGEN-RUECKME KUNST S

End position feedback plastic- inductive sensors

**HANSA FLEX**

## Eigenschappen

<b>Bedrijfsstroom</b>	200 mA
<b>Kabelschroefverbinding</b>	M 20 x 1.5
<b>Schakelfunctie</b>	Positive switching, PNP NO contact, damped or undamped in the end position
<b>Beschermingsklasse</b>	IP 67, acc. to DIN EN 60529
<b>Temperatuurgebied</b>	-20 °C to +70 °C
<b>Behuizing</b>	Polyamide blue or black
<b>Schroef</b>	Stainless steel 1.4301
<b>As</b>	Polyamide PA6, black
<b>Deksel</b>	Polycarbonate, transparent
<b>Montagebrug</b>	PA6 with 30 % glass fibre
<b>Afdichtingen</b>	EPDM and NBR
<b>Afdichtmateriaal</b>	NBR



## Aanwijzing

Andere gegevens op aanvraag.

## Beschrijving

Robust type in a plastic housing, Universal indicator for NAMUR sizes 80 x 30 and 130 x 30, Height-adjustable feet that adapt to different pinion projections, ON / OFF position indicator also visible from a distance, Easy-to-adjust, self-locking trip cam

## Artikel

Aanduiding	Spanning	Definitie
K- 07 30 29 06	9 V - 36 V DC	End position feedback, D 2 type with inductive 3-wire sensors