

# K-VT 2 ABGAENGE G

Manifolds

**HANSA FLEX**

## Eigenschappen

|                      |                        |
|----------------------|------------------------|
| Ingangsdruk          | 0 - 9 bar              |
| Mediumtemperatuur    | max. 70 °C             |
| Omgevingstemperatuur | Max. 70 °C             |
| Afdichtmateriaal     | NBR                    |
| Behuizing            | Die-cast aluminium     |
| Overige gegevens     | User manual on request |



## Artikel

| Aanduiding     | Schroefdraad | A<br>(mm) | B       | C<br>(mm) | D<br>(mm) | Maat |
|----------------|--------------|-----------|---------|-----------|-----------|------|
| K- 07 25 12 19 | G 1/4        | 35,0      | 44,0 mm | 22,0      | 22,0      | 200  |
| K- 07 25 12 20 | G 3/8        | 35,0      | 44,0 mm | 22,0      | 22,0      | 200  |
| K- 07 25 12 21 | G 3/8        | 42,0      | 52,0 mm | 26,0      | 26,0      | 300  |
| K- 07 25 12 22 | G 1/2        | 42,0      | 52,0 mm | 26,0      | 26,0      | 300  |
| K- 07 25 12 23 | G 3/4        | 60,0      | 76,0 mm | 38,0      | 38,0      | 600  |
| K- 07 25 12 24 | G 1          | 60,0      | 76,0 mm | 38,0      | 38,0      | 600  |

## Toebehoren

|                      |                 |
|----------------------|-----------------|
| K-VERBINDUNGELEMENTE | Connecting sets |
| K-WANDHALTER         | Wall bracket    |