

# K-KALIBRIER-TEST UND SERVICE

Calibration, testing and service unit

**HANSA FLEX**

## Eigenschappen

Uitvoering	Calibration, testing and service unit
Nauwkeurigheid	0,25% FS
Meetstoftemperatuur	-20 °C to +80 °C
Omgevingstemperatuur	-10 °C to +50 °C
Met meetstof in aanraking zijnde onderdelen	CrNi-steel with NBR seal
Behuizing	Die-cast zinc



## Aanwijzing

Andere gegevens op aanvraag.

## Beschrijving

Service case for quick and precise pressure gauge calibration. Suitable for service and maintenance providers of all kinds as well as instrumentation control workshops and quality assurance. Simple operation using four buttons. The high sampling rate (100 measurements / second) guarantees an accurate analysis at the measuring point. Comprised of a CPG500 digital gauge and a CPP40 pneumatic hand test pump with a connecting cable for pressure generation. Operating manual, calibration certificate 3.1, two AA batteries and a protective rubber cap for the housing are enclosed. Includes a plastic emergency case with foam padding.

## Extra informatie

Further measuring ranges on request

## Artikel

Aanduiding	Meetbereik	Aansluiting
K- 07 20 12 70	-0.95 / +40 bar	G 1/4