K-DRS ELEKTRONISCH

Pressure switches, electronic with digital display

HANSA FLEX

Eigenschappen

Omgevingstemperatuur	-20 °C to +80 °C
Elektrische aansluiting	Ronde connector M 12 x 1, 4-pol.
Uitgangssignaal	2 switching outputs
Nauwkeurigheid	1% of span
Hulpenergie	DC 15 - 35V
Met meetstof in aanraking zijnde onderdelen	CrNi steel
Meetstoftemperatuur	-20 °C to +85 °C
Procesaansluiting	G 1/4
Beschermingsklasse	IP 65 and IP 67 (M 12 x 1)
Behuizing	CrNi steel

Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

Electronic pressure switch with digital display, made of stainless steel, for monitoring and measuring pressures in liquids, gases or compressed air.
Applications: Machine tools, compressors and pumps, hydraulic and pneumatic systems, machinery in general

Artikel

Aanduiding	Aansluiting	Meetbereik
K- 07 30 30 07	G 1/4	0 - 1.0 bar
K- 07 30 30 12	G 1/4	0 - 2.5 bar
K- 07 30 30 15	G 1/4	0 - 4.0 bar
K- 07 30 30 18	G 1/4	0 - 6.0 bar
K- 07 30 30 08	G 1/4	0 - 10.0 bar
K- 07 30 30 10	G 1/4	0 - 16.0 bar
K- 07 30 30 13	G 1/4	0 - 25.0 bar
K- 07 30 30 16	G 1/4	0 - 40.0 bar
K- 07 30 30 19	G 1/4	0 - 60.0 bar
K- 07 30 30 09	G 1/4	0 - 100.0 bar
K- 07 30 30 11	G 1/4	0 - 160.0 bar
K- 07 30 30 14	G 1/4	0 - 250.0 bar
K- 07 30 30 17	G 1/4	0 - 400.0 bar
K- 07 30 30 20	G 1/4	0 - 600.0 bar

Toebehoren

K-ELEKTRO DRUCHSCHALTER EDS	Electronic pressure switch EDS

Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.