K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges, CrNi steel type

Eigenschappen

Type	233.50
Uitvoering	Glycerine-filled bourdon-tube pressure gauge, CrNi steel type
Toepassing	For gaseous or liquid, corrosive and crystallising mediawhich do not have high viscosity, also in corrosive atmosphere
Kwaliteitsklasse	1.6 (Ø 63 mm), 1.0 (Ø 100 mm and Ø 160 mm)
Mediumtemperatuur	max. +100 °C
Omgevingstemperatuur	-20 °C tot +60 °C
Behuizing	CrNi steel
Kijkglas	Laminated safety glass Ø 63 = Polycarbonate



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

For use in the chemical/petrochemical process industry, power stations, machinery and industrial plant engineering. For measuring points with high dynamic pressure loads and vibrations.

Artikel

Aanduiding	Meetbereik	Ø (mm)	Aansluiting
K- 07 20 11 93	-1 / 0.0 bar	63,0	G 1/4“
K- 07 20 11 95	-1 / +0.6 bar	63,0	G 1/4“
K- 07 20 11 97	-1 / +1.5 bar	63,0	G 1/4“
K- 07 20 11 99	-1 / +3.0 bar	63,0	G 1/4“
K- 07 20 12 01	-1 / +5.0 bar	63,0	G 1/4“
K- 07 20 12 03	-1 / +9.0 bar	63,0	G 1/4“
K- 07 20 12 05	-1 / +15.0 bar	63,0	G 1/4“
K- 07 20 12 08	0 - 1.0 bar	63,0	G 1/4“
K- 07 20 12 10	0 - 1.6 bar	63,0	G 1/4“
K- 07 20 12 12	0 - 2.5 bar	63,0	G 1/4“
K- 07 20 12 14	0 - 4.0 bar	63,0	G 1/4“
K- 07 20 12 16	0 - 6.0 bar	63,0	G 1/4“
K- 07 20 12 18	0 - 10.0 bar	63,0	G 1/4“
K- 07 20 12 20	0 - 16.0 bar	63,0	G 1/4“
K- 07 20 12 22	0 - 25.0 bar	63,0	G 1/4“
K- 07 20 12 24	0 - 40.0 bar	63,0	G 1/4“
K- 07 20 12 26	0 - 60.0 bar	63,0	G 1/4“
K- 07 20 12 28	0 - 100.0 bar	63,0	G 1/4“
K- 07 20 12 30	0 - 160.0 bar	63,0	G 1/4“
K- 07 20 12 32	0 - 250.0 bar	63,0	G 1/4“
K- 07 20 12 34	0 - 400.0 bar	63,0	G 1/4“
K- 07 20 12 36	0 - 600.0 bar	63,0	G 1/4“
K- 07 20 11 92	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 11 94	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 11 96	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 11 98	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 12 00	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 12 02	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 12 04	-1 / +15.0 bar	100,0	G 1/2"
K- 07 20 12 06	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 12 07	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 12 09	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 12 11	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 12 13	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 12 15	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 12 17	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 12 19	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 12 21	0 - 25.0 bar	100,0	G 1/2"

Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.

K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges, CrNi steel type

HANSA-FLEX

Artikel

Aanduiding	Meetbereik	Ø (mm)	Aansluiting
K- 07 20 12 23	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 12 25	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 12 27	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 12 29	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 12 31	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 12 33	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 12 35	0 - 600.0 bar	100,0	G 1/2"
K- 07 20 03 48	0 - 0.6 bar	160,0	G 1/2"
K- 07 20 03 49	0 - 1.0 bar	160,0	G 1/2"
K- 07 20 03 50	0 - 1.6 bar	160,0	G 1/2"
K- 07 20 03 51	0 - 2.5 bar	160,0	G 1/2"
K- 07 20 03 52	0 - 4.0 bar	160,0	G 1/2"
K- 07 20 03 53	0 - 6.0 bar	160,0	G 1/2"
K- 07 20 03 54	0 - 10.0 bar	160,0	G 1/2"
K- 07 20 03 55	0 - 16.0 bar	160,0	G 1/2"
K- 07 20 03 56	0 - 25.0 bar	160,0	G 1/2"
K- 07 20 03 57	0 - 40.0 bar	160,0	G 1/2"
K- 07 20 03 58	0 - 60.0 bar	160,0	G 1/2"
K- 07 20 03 59	0 - 100.0 bar	160,0	G 1/2"
K- 07 20 03 60	0 - 160.0 bar	160,0	G 1/2"
K- 07 20 03 61	0 - 250.0 bar	160,0	G 1/2"
K- 07 20 03 62	0 - 400.0 bar	160,0	G 1/2"
K- 07 20 03 63	0 - 600.0 bar	160,0	G 1/2"

Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.