K-DMUF ALLGEMEIN

Pressure transmitters for universal industrial applications, nonlinearity 0.25%

Eigenschappen

Type	S-20
Spanning	DC 8 ... 36 V
Elektrische aansluiting	With right-angle connector acc. to DIN EN 175301-803 A
Beschermingsklasse	IP 65 acc. to EN 60529
Uitgangssignaal	4 to 20 mA, 2-wire
Niet-lineariteit	up to 0.25% of span
Mediumtemperatuur	-30 °C to +100 °C
Omgevingstemperatuur	-40 °C to +70 °C
Met meetstof in aanraking zijnde onderdelen	CrNi steel 1.4571
Behuizing	CrNi steel 1.4571



Beschrijving

Pressure transmitters, very high precision, in CrNi steel, for complex measurement tasks in the process industry as well as research and development. Applications: Low temperature or outdoor applications, extreme shock loads and vibration levels, corrosive media in the chemical industry. Compatible with all internationally established process connections.

Extra informatie

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

Artikel

Aanduiding	Meetbereik	Schroefdraad
K- 07 20 12 55	-1 / 0.0 bar	G 1/2
K- 07 20 12 56	0 - 0.4 bar	G 1/2
K- 07 20 12 57	0 - 1.0 bar	G 1/2
K- 07 20 12 64	0 - 4.0 bar	G 1/2
K- 07 20 12 67	0 - 6.0 bar	G 1/2
K- 07 20 12 58	0 - 10.0 bar	G 1/2
K- 07 20 12 60	0 - 16.0 bar	G 1/2
K- 07 20 12 62	0 - 25.0 bar	G 1/2
K- 07 20 12 65	0 - 40.0 bar	G 1/2
K- 07 20 12 68	0 - 60.0 bar	G 1/2
K- 07 20 12 59	0 - 100.0 bar	G 1/2
K- 07 20 12 61	0 - 160.0 bar	G 1/2
K- 07 20 12 63	0 - 250.0 bar	G 1/2
K- 07 20 12 66	0 - 400.0 bar	G 1/2
K- 07 20 12 69	0 - 600.0 bar	G 1/2

Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.