



# K-W90 AG-K ISO 7-1 VA

Male elbows, conical male thread acc. to ISO 7-1, stainless steel

**HANSA FLEX**

## Eigenschappen

Drukbereik	Max. 25 bar
aanbevolen slangen	PTFE hose
Temperatuurgebied	-40 °C to +200 °C (depending on the hose quality and diameter)
Materiaal	RVS 1.4404
Afdichting	Pure metal



## Aanwijzing

Andere gegevens op aanvraag.

## Beschrijving

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

## Artikel

Aanduiding	Schroefdraad	voor slang	L1 (mm)	L2 (mm)	SW1 (mm)	SW2 (mm)
K- 07 40 30 32	R 1/8	6 mm / 4 mm	23,0	17,0	12	10
K- 07 40 30 33	R 1/8	8 mm / 6 mm	23,0	17,0	14	10
K- 07 40 30 30	R 1/4	6 mm / 4 mm	23,0	21,5	12	10
K- 07 40 30 31	R 1/4	8 mm / 6 mm	23,0	21,5	14	10
K- 07 40 30 29	R 1/4	10 mm / 8 mm	26,0	21,5	16	12