# K-SCHLAUCH KUPPLUNG SET STAN

Hose and coupling kits, with straight hose and DN 7.6 standard coupling

## Eigenschappen

| | |
|---|---|
| **Werkdruk** | 16 bar |
| **Mediumtemperatuur** | -20 °C to +60 °C |



## Aanwijzing

Andere gegevens op aanvraag.

## Beschrijving

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

## Artikel

| Aanduiding | Slangmaat | Werklengte (m) |
|---|---|---|
| **K- 07 10 05 62** | 12 mm x 8 mm | 10,0 |
| **K- 07 10 05 63** | 12 mm x 8 mm | 15,0 |
| **K- 07 10 05 64** | 16 mm x 11 mm | 10,0 |
| **K- 07 10 05 65** | 16 mm x 11 mm | 15,0 |

*Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.*