

# K-WV 3/2 LB NAMUR GETAUSCHT

3/2-way spool valves with NAMUR style interface, NC, ports 1 and 3 or 2 and 3 swapped

**HANSA FLEX**

## Eigenschappen

Middelen	Air, neutral gases, filtered
Werkdruk	1.5 to 10 bar
Bedrijfstemperatuur	-20 °C to +70 °C
Elektrische aansluiting	Plug connector PG 9
Bij de levering inbegrepen	Plug connector PG 9, 1 coding pin, 2 O-rings, 2 fixing screws
Opgenomen vermogen	3 W=5 VA~
Behuizing	Aluminium, anodised
Schuif	Stainless steel
Afdichtmateriaal	NBR



## Aanwijzing

Andere gegevens op aanvraag.

## Beschrijving

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

Two or three-piece service units with excellent flow rates in modern design. <br>Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.<br>

## Artikel

Aanduiding	Spanning	Aansluiting	DN	Debiet (L/min)
K- 07 15 00 05	230 V, 50 Hz	G 1/4	7	1250
K- 07 15 00 06	24 V DC	G 1/4	7	1250