

K-WV 3/2 LB NAMUR GETAUSCHT

3/2-way spool valves with NAMUR style interface, NC, ports 1 and 3 or 2 and 3 swapped

HANSA FLEX

Eigenschappen

| | |
|----------------------------|---------------------------------------------------------------|
| Middelen | Air, neutral gases, filtered |
| Werkdruk | 1.5 to 10 bar |
| Bedrijfstemperatuur | -20 °C to +70 °C |
| Elektrische aansluiting | Plug connector PG 9 |
| Bij de levering inbegrepen | Plug connector PG 9, 1 coding pin, 2 O-rings, 2 fixing screws |
| Opgenomen vermogen | 3 W=5 VA~ |
| Behuizing | Aluminium, anodised |
| Schuif | Stainless steel |
| Afdichtmateriaal | NBR |



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

Two or three-piece service units with excellent flow rates in modern design.
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Artikel

| Aanduiding | Spanning | Aansluiting | DN | Debiet (L/min) |
|----------------|--------------|-------------|----|----------------|
| K- 07 15 00 05 | 230 V, 50 Hz | G 1/4 | 7 | 1250 |
| K- 07 15 00 06 | 24 V DC | G 1/4 | 7 | 1250 |