


K-SVKM NW 7,2 IG VA

Quick disconnect couplings DN 7.2, stainless steel, female

HANSA FLEX

Eigenschappen

Werkdruk	1 - 35 bar and rough vacuum
Debiet lucht	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Mediumtemperatuur	-25 °C to +200 °C
Behuizing, huls, ventielhuis	Stainless steel 1.4305
Veer, snapring	Stainless steel 1.4310
Vergrendelingspennen	Stainless steel 1.4401
Afdichtmateriaal	FKM



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

Classic standard coupling type, one side sealing, made of stainless steel. The closed sleeve protects the coupling from dirt. We recommend the use of stainless steel plugs and stems!

Artikel

Aanduiding	Aansluiting	Lengte (mm)	SW (mm)
K- 07 35 07 62	G 1/4 female	43,0	22
K- 07 35 07 63	G 3/8 female	43,0	22
K- 07 35 07 64	G 1/2 female	46,0	24

Extra elementen

K-NIPPEL KUPPL NW7 AG VA 2	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male
K-NIPPEL KUPPL NW7 IG VA 1	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female
K-TUE 7,2 7,8 VA 2	Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305