

K-SVKM NW 7,8 SCHL TUE H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem

HANSA FLEX

Eigenschappen

Werkdruk	0 - 35 bar
Debiet lucht	2.100 l/min (at $\Delta p = 0.5$ bar)
Mediumtemperatuur	-20 °C to +40 °C
Draadstuk	Nickel-plated brass
Ventielhuis	Steel, QPQ treated
Ontgrendelingshuls	Extremely robust, ergonomic plastic
Ventiel, zitting	Brass
Middelen	Only for clean compressed air
Afdichtingen	NBR
Veer, snapping, kogels	stain less steel



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Artikel

Aanduiding	Aansluiting	Lengte (mm)	SW (mm)
K- 07 35 08 53	Stem, I.D. 6	80,0	19
K- 07 35 12 41	Stem, I.D. 8	80,0	19
K- 07 35 08 54	Stem, I.D. 9	80,0	19
K- 07 35 12 42	Stem, I.D. 10	80,0	19
K- 07 35 08 55	Stem, I.D. 13	80,0	19

Extra elementen

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass