

K-LKM S NW7,8 SCHL TUE

Safety couplings DN 7.8, with hose stem

HANSA FLEX

Eigenschappen

Werkdruk	max. 20 bar
Debiet lucht	1.400 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Mediumtemperatuur	-20 °C to +100 °C
Aansluiting ventielelement	Nickel-plated brass
Veer, kogels	Stainless-steel
Glijbus	Anodised aluminium
Ontgrendelingshuls	Hardened and nickel-plated steel
Afdichtmateriaal	NBR



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

Artikel

Aanduiding	Aansluiting	Lengte (mm)
K- 07 35 08 88	Stem, I.D. 6	86,0
K- 07 35 12 96	Stem, I.D. 8	86,0
K- 07 35 08 89	Stem, I.D. 9	86,0
K- 07 35 12 97	Stem, I.D. 10	86,0
K- 07 35 08 90	Stem, I.D. 13	86,0

Extra elementen

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 5 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass