K-SENSOREN T-NUT 1

Sensor for T-slot



Extra informatie

Important: The scope of supply does not include a connector. Please order separately.
Adjustable limit switches with shock absorber available on request.

Artikel

Aanduiding	Uitvoering
K- 07 15 20 89	Reed sensor, 2-wire, with 2.5 m cable length
K- 07 15 20 90	Reed sensor, 2-wire, with M 8 plug (3-pin)
K- 07 15 20 93	Hall sensor, 3-wire, with M 8 plug (3-pin)

is toebehoren bij volgende producten

K-RUNDZYLINDER DOPP O E D	Round cylinders, double acting, magnetic, non-cushioned
K-RUNDZYLINDER DOPP O D	Miniature cylinders, double acting (magnetic, non-cushioned)
K-RUNDZYLINDER EINF O D	Miniature cylinders, single-acting (magnetic, non-cushioned)
K-RUNDZYLINDER DOPP O D 1	Round cylinders, double acting (magnetic, non-cushioned)
K-NORMZYLINDER	Standard cylinders
K-KOLST LOSE ZYL	Rodless cylinders

Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.