

K-MV G (NC) D 24 V DC H

Normally closed, (NC), directly operated, 24 V DC, for high pressures

HANSA FLEX

Eigenschappen

Elektrische aansluiting	device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket
Schroefdraad beschrijving	G thread acc. DIN EN ISO 228-1
Mediumtemperatuur	max. 80 °C when using water or oils; max. 90 °C when using with air
Beschermingsklasse	IP 65
max. bedrijfsdruk	30 bar
Afdichtmateriaal	FPM
Behuizing, ventielzitting	Stainless steel 1.4301
Inwendige delen	Stainless steel



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

Standard series in two different versions: Directly operated, Pilot-operated

Artikel

Aanduiding	Schroefdraad	NW	A (mm)	B (mm)	C (mm)	Constructie
K- 07 30 01 24	G 1/8	1,5	70,0	40,0	70,7	1
K- 07 30 01 25	G 1/4	1,5	70,0	40,0	70,7	1
K- 07 30 01 26	G 3/8	3,0	85,0	52,0	87,0	1
K- 07 30 01 27	G 1/2	3,0	85,0	52,0	87,0	1