


K-WTEH 3-TLG PC-BEHÄLTER S W H G-MINI

Service units, 3-piece with polycarbonate bowl, bowl guard and joiner for wall mounting, semi-automatic drain valve

HANSA FLEX

Eigenschaften

| | |
|----------------------------------|----------------------------------------------------------------|
| Ingangsdruk | Max. 10 bar |
| Mediumtemperatuur | max. 70 °C |
| Omgevingstemperatuur | Max. 70 °C |
| Poriënwijde in het filterelement | 5 µm |
| Afdichtmateriaal | NBR |
| Veerkap | POM |
| Behuizing | Die-cast aluminium |
| Druppelopzet | Brass/POM |
| Drain valve | Semi-automatic |
| Debietwaardemeting | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Overige gegevens | User manual on request |



Artikel

| Aanduiding | Schroefdraad | Regelbereik | Debiet (L/min) | A (mm) | B | C (mm) | D (mm) | Maat |
|----------------|--------------|-------------|----------------|--------|----------|--------|--------|------|
| K- 07 25 14 35 | G 1/8 | 1.5 - 9 bar | 500 | 138,0 | 132,0 mm | 39,0 | 93,0 | 200 |
| K- 07 25 14 36 | G 1/4 | 1.5 - 9 bar | 500 | 138,0 | 132,0 mm | 39,0 | 93,0 | 200 |

Toebehoren

| | |
|------------------------------------|---------------------------------------------------------|
| K-VERSCHLEI-SATZ | Set of wearing parts |
| K-ERSATZMEMBRANE | Replacement diaphragm |
| K-ADAPTERPLATTEN HANSA | Adapter plate HANSA |
| K-FILTERELEMENT | Filter element |
| K-ERSATZBEHÄLTER G UND G-MINI POLY | Spare tanks »G« Series and »G-mini« Series Polycarbonat |
| K-VERBINDUNGSELEMENTE | Connecting sets |
| K-WANDHALTER | Wall bracket |