


# K-LKM S NW7,6 AG

Safety couplings DN 7.6, male

**HANSA FLEX**

## Eigenschappen

Werkdruk	Max. 16 bar
Debiet lucht	2.250 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Mediumtemperatuur	-20 °C to +100 °C
Materiaal	Galvanised steel / brass
Veer	Stainless-steel
Afdichtmateriaal	NBR



## Aanwijzing

Andere gegevens op aanvraag.

## Beschrijving

High-quality, robust and durable, one-hand quick disconnect safety couplings, with very high flow rates and only a small pressure drop. The coupling is released fully automatically in two steps. Air is relieved from the coupling before it is completely disconnected, to minimise the risk of injury to the operator from hose ends flying around. The plug is only disconnected from the coupling if the residual pressure has dropped below 0.3 bar. The dreaded "whiplash effect" is thus avoided and the risk of injury virtually eliminated. This safety version conforms to ISO-Standard DIN EN ISO 4414.

## Artikel

Aanduiding	Aansluiting	Lengte (mm)	SW (mm)
K- 07 35 13 19	R 1/4 male	63,0	20
K- 07 35 13 21	R 3/8 male	61,0	20
K- 07 35 13 16	R 1/2 male	55,5	22

## Extra elementen

K-NIPPEL KUPPL NW7 AG VZ PTFE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-NIPPEL KUPPL STREAM LINE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel »stream line«
K-TUE 7,2 7,8 ST VZ 2	Stems for couplings DN 7.2 - DN 7.8, hardened and galvanised steel