

# K-WTEH 2-TLG MET SICHT WAND H G

Service units, 2-piece with metal bowl, sight glass and joiner for wall mounting, semi-automatic drain valve

**HANSA FLEX**

## Eigenschappen

|                                  |                                                                |
|----------------------------------|----------------------------------------------------------------|
| Ingangsdruk                      | Max. 10 bar                                                    |
| Mediumtemperatuur                | max. 70 °C                                                     |
| Omgevingstemperatuur             | Max. 70 °C                                                     |
| Poriënwijde in het filterelement | 5 µm                                                           |
| Afdichtmateriaal                 | NBR                                                            |
| Veerkap                          | POM                                                            |
| Behuizing                        | Die-cast aluminium                                             |
| Druppelopzet                     | Brass/POM                                                      |
| Drain valve                      | Semi- or fully-automatic                                       |
| Debietwaardemeting               | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Overige gegevens                 | User manual on request                                         |



## Artikel

| Aanduiding     | Schroefdraad | Regelbereik | Debiet (L/min) | A (mm) | B        | C (mm) | D (mm) | Maat |
|----------------|--------------|-------------|----------------|--------|----------|--------|--------|------|
| K- 07 25 14 05 | G 3/4        | 1.5 - 9 bar | 4200           | 190,0  | 363,0 mm | 144,0  | 219,0  | 600  |
| K- 07 25 14 07 | G 1          | 1.5 - 9 bar | 4200           | 190,0  | 363,0 mm | 144,0  | 219,0  | 600  |

## Toebehoren

|                                     |                                                          |
|-------------------------------------|----------------------------------------------------------|
| K-VERSCHLEI-SATZ                    | Set of wearing parts                                     |
| K-ERSATZMEMBRANE                    | Replacement diaphragm                                    |
| K-ADAPTERPLATTEN HANSA              | Adapter plate HANSA                                      |
| K-FILTERELEMENT                     | Filter element                                           |
| K-ERSATZBEHAELTER G UND G-MINI POLY | Spare tanks »G« Series and »G-minik« Series Polycarbonat |
| K-VERBINDUNGELEMENTE                | Connecting sets                                          |
| K-WANDHALTER                        | Wall bracket                                             |