

K-L-MEHRFACHVERT 4 DR AGR OR

Multiple union elbows with outer hex, 4 outlets, swivel type, parallel male thread with O-ring

HANSA FLEX

Eigenschappen

Werkdruk	Max. 15 bar, coarse vacuum
Toepassingsgebied	Air, vacuum
aanbevolen slangen	PU or PA (nylon)
Middelen	Compressed air and all gases or liquids that are compatible with the materials
Temperatuurgebied	-20 °C to +80 °C
Dichtvlak	Parallel version: O-ring in housing
Materiaal	Plastic, Nickel plated brass
Aandrukking	Plastic



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Artikel

Aanduiding	Schroefdraad	voor uitw. slang-Ø	L1 (mm)	L2 (mm)	SW
K- 07 40 43 29	G 1/8	6 mm	41,0	24,0	12 mm
K- 07 40 43 30	G 1/8	8 mm	44,0	28,5	14 mm
K- 07 40 43 27	G 1/4	6 mm	43,0	24,0	14 mm
K- 07 40 43 28	G 1/4	8 mm	46,0	28,5	17 mm
K- 07 40 43 26	G 1/4	10 mm	55,5	33,7	19 mm
K- 07 40 43 31	G 3/8	10 mm	56,5	33,7	19 mm
K- 07 40 43 32	G 3/8	12 mm	63,5	37,5	24 mm
K- 07 40 43 25	G 1/2	12 mm	65,0	37,5	24 mm