

K-ROHRDOPPELNIPPEL 23 AG ST37 VZ

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982

HANSA FLEX

Eigenschappen

Werkdruk	Max. 50 bar
Oppervlak	Hot dip galvanised
Aansluitschroefdraad	acc. ISO 7-1
Materiaal	Zinc plated steel ST 37-2



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

Artikel

Aanduiding	Schroefdraad	Lengte (mm)
K- 07 40 35 71	R 1/4	40,0
K- 07 40 35 72	R 1/4	60,0
K- 07 40 35 73	R 1/4	80,0
K- 07 40 35 66	R 1/4	100,0
K- 07 40 35 67	R 1/4	120,0
K- 07 40 35 68	R 1/4	150,0
K- 07 40 35 69	R 1/4	180,0
K- 07 40 35 70	R 1/4	200,0
K- 07 40 35 95	R 3/8	40,0
K- 07 40 35 96	R 3/8	60,0
K- 07 40 35 97	R 3/8	80,0
K- 07 40 35 90	R 3/8	100,0
K- 07 40 35 91	R 3/8	120,0
K- 07 40 35 92	R 3/8	150,0
K- 07 40 35 93	R 3/8	180,0
K- 07 40 35 94	R 3/8	200,0
K- 07 40 35 63	R 1/2	40,0
K- 07 40 35 64	R 1/2	60,0
K- 07 40 35 65	R 1/2	80,0
K- 07 40 35 58	R 1/2	100,0
K- 07 40 35 59	R 1/2	120,0
K- 07 40 35 60	R 1/2	150,0
K- 07 40 35 61	R 1/2	180,0
K- 07 40 35 62	R 1/2	200,0
K- 07 40 35 87	R 3/4	40,0
K- 07 40 35 88	R 3/4	60,0
K- 07 40 35 89	R 3/4	80,0
K- 07 40 35 82	R 3/4	100,0
K- 07 40 35 83	R 3/4	120,0
K- 07 40 35 84	R 3/4	150,0
K- 07 40 35 85	R 3/4	180,0
K- 07 40 35 86	R 3/4	200,0
K- 07 40 35 39	R 1	40,0
K- 07 40 35 40	R 1	60,0
K- 07 40 35 41	R 1	80,0
K- 07 40 35 34	R 1	100,0
K- 07 40 35 35	R 1	120,0
K- 07 40 35 36	R 1	150,0



Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.

25.04.2026

HANSA-FLEX AG

www.hansa-flex.com

1

K-ROHRDOPPELNIPPEL 23 AG ST37 VZ

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982



Artikel		
Aanduiding	Schroefdraad	Lengte (mm)
K- 07 40 35 37	R 1	180,0
K- 07 40 35 38	R 1	200,0
K- 07 40 35 55	R 1 1/4	40,0
K- 07 40 35 56	R 1 1/4	60,0
K- 07 40 35 57	R 1 1/4	80,0
K- 07 40 35 50	R 1 1/4	100,0
K- 07 40 35 51	R 1 1/4	120,0
K- 07 40 35 52	R 1 1/4	150,0
K- 07 40 35 53	R 1 1/4	180,0
K- 07 40 35 54	R 1 1/4	200,0
K- 07 40 35 47	R 1 1/2	40,0
K- 07 40 35 48	R 1 1/2	60,0
K- 07 40 35 49	R 1 1/2	80,0
K- 07 40 35 42	R 1 1/2	100,0
K- 07 40 35 43	R 1 1/2	120,0
K- 07 40 35 44	R 1 1/2	150,0
K- 07 40 35 45	R 1 1/2	180,0
K- 07 40 35 46	R 1 1/2	200,0
K- 07 40 35 79	R 2	40,0
K- 07 40 35 80	R 2	60,0
K- 07 40 35 81	R 2	80,0
K- 07 40 35 74	R 2	100,0
K- 07 40 35 75	R 2	120,0
K- 07 40 35 76	R 2	150,0
K- 07 40 35 77	R 2	180,0
K- 07 40 35 78	R 2	200,0
K- 07 40 50 93	R 2 1/2	80,0
K- 07 40 50 88	R 2 1/2	100,0
K- 07 40 50 89	R 2 1/2	120,0
K- 07 40 50 90	R 2 1/2	150,0
K- 07 40 50 91	R 2 1/2	180,0
K- 07 40 50 92	R 2 1/2	200,0
K- 07 40 50 99	R 3	80,0
K- 07 40 50 94	R 3	100,0
K- 07 40 50 95	R 3	120,0
K- 07 40 50 96	R 3	150,0
K- 07 40 50 97	R 3	180,0
K- 07 40 50 98	R 3	200,0