K-GMM 2

Glycerine-filled pressure gauges, CrNi steel type

Eigenschappen

Type	233.30
Uitvoering	Glycerine-filled Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)
Toepassing	For gaseous or liquid, corrosive and crystallising mediawhich do not have high viscosity, also in corrosive atmosphere
Kwaliteitsklasse	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
Mediumtemperatuur	max. +100 °C
Omgevingstemperatuur	-20 °C tot +60 °C
Behuizing	CrNi steel
Kijkglas	Laminated safety glass Ø 63 = Polycarbonate



Aanwijzing

Andere gegevens op aanvraag.

Artikel

Aanduiding	Meetbereik	Ø (mm)	Aansluiting
K- 07 20 07 03	-1 / 0.0 bar	63,0	G 1/4“
K- 07 20 07 04	0 - 4.0 bar	63,0	G 1/4“
K- 07 20 07 05	0 - 6.0 bar	63,0	G 1/4“
K- 07 20 07 06	0 - 10.0 bar	63,0	G 1/4“
K- 07 20 07 07	0 - 16.0 bar	63,0	G 1/4“
K- 07 20 07 08	0 - 25.0 bar	63,0	G 1/4“
K- 07 20 07 09	0 - 40.0 bar	63,0	G 1/4“
K- 07 20 07 10	0 - 60.0 bar	63,0	G 1/4“
K- 07 20 07 11	0 - 100.0 bar	63,0	G 1/4“
K- 07 20 07 12	0 - 160.0 bar	63,0	G 1/4“
K- 07 20 07 13	0 - 250.0 bar	63,0	G 1/4“
K- 07 20 07 14	0 - 400.0 bar	63,0	G 1/4“
K- 07 20 01 79	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 01 80	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 01 81	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 01 82	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 01 83	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 01 84	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 01 85	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 01 86	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 01 87	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 01 88	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 01 89	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 01 90	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 01 91	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 01 92	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 01 93	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 01 94	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 01 95	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 01 96	0 - 600.0 bar	100,0	G 1/2"

Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.