


# K-LKM S NW7,4 DREH AG VA

Safety couplings DN 7.4, stainless steel 1.4404, male, swivel type

**HANSA FLEX**

## Eigenschappen

Werkdruk	max. 10 bar
Debiet lucht	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Mediumtemperatuur	-20 °C to +150 °C
Behuizing	Stainless steel 1.4404
Schroefdraad	Stainless steel 1.4404
Inwendige delen	Stainless steel 1.4404
Knop, ventiel	Stainless steel 1.4404
Afdichtmateriaal	FKM



## Aanwijzing

Not suitable for hitting / pulsating tools.

Andere gegevens op aanvraag.

## Beschrijving

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

## Extra informatie

Not suitable for hitting / pulsating tools.

## Artikel

Aanduiding	Aansluiting	Lengte (mm)	SW (mm)
K- 07 35 12 76	G 1/4 male	70,5	21
K- 07 35 12 77	G 3/8 male	70,0	21
K- 07 35 12 78	G 1/2 male	72,5	25