

# K-STECKVERSCHR IG SK

Male connectors, parallel female thread with outer hex

**HANSA FLEX**

## Eigenschappen



Werkdruk Max. 16 bar

Bedrijfstemperatuur -20 °C to +80 °C

Materiaal messing vernikkeld

Aandrukkring Hostaform

Spanring Stainless steel



## Aanwijzing

Andere gegevens op aanvraag.

## Beschrijving

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Artikel

| Aanduiding     | Schroefdraad | voor uitw. slang-Ø | L1<br>(mm) | SW    |
|----------------|--------------|--------------------|------------|-------|
| K- 07 40 25 06 | M 5          | 3 mm               | 15,7       | 7 mm  |
| K- 07 40 25 12 | G 1/8        | 4 mm               | 26,2       | 10 mm |
| K- 07 40 25 13 | G 1/8        | 5 mm               | 27,5       | 12 mm |
| K- 07 40 25 14 | G 1/8        | 6 mm               | 27,1       | 12 mm |
| K- 07 40 25 15 | G 1/8        | 8 mm               | 28,1       | 13 mm |
| K- 07 40 25 09 | G 1/4        | 4 mm               | 28,6       | 10 mm |
| K- 07 40 47 15 | G 1/4        | 5 mm               | 29,5       | 12 mm |
| K- 07 40 25 10 | G 1/4        | 6 mm               | 29,3       | 12 mm |
| K- 07 40 25 11 | G 1/4        | 8 mm               | 30,0       | 14 mm |
| K- 07 40 25 08 | G 1/4        | 10 mm              | 31,8       | 16 mm |
| K- 07 40 25 16 | G 3/8        | 10 mm              | 36,8       | 16 mm |
| K- 07 40 25 17 | G 3/8        | 12 mm              | 37,0       | 19 mm |
| K- 07 40 25 07 | G 1/2        | 12 mm              | 40,5       | 19 mm |