

K-LKM S NW7,2 AG

Safety couplings DN 7.2, male

HANSA FLEX

Eigenschappen

Werkdruk	0 - 35 bar, maximum static working pressure (non-pulsating)
Debiet lucht	1.100 l/min (at $\Delta p = 0.5$ bar)
Mediumtemperatuur	-30 °C to +100 °C
Behuizing, huls, ventielhuis	Nickel-plated brass
Veer, kogels	Stainless-steel
Afdichtmateriaal	NBR



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

One-hand safety coupling with double locking mechanism. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the unlocking sleeve again. The coupling can now be disconnected.

Artikel

Aanduiding	Aansluiting	Lengte (mm)	SW (mm)
K- 07 35 02 92	G 1/4 male	44,0	22
K- 07 35 02 93	G 3/8 male	44,0	22
K- 07 35 02 94	G 1/2 male	47,0	24

Extra elementen

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,