

K-T-STECK VB 3

Union tees

HANSA FLEX

Eigenschappen

| | |
|---------------------|--------------------|
| Werkdruk | Max. 16 bar |
| Bedrijfstemperatuur | -20 °C to +80 °C |
| Materiaal | messing vernikkeld |
| Aandrukkring | Hostaform |
| Spanring | Stainless steel |



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Artikel

| Aanduiding | voor uitw. slang-Ø | L1 (mm) | L2 (mm) |
|----------------|--------------------|------------|------------|
| K- 07 40 25 42 | 3 mm | 21,2 | 10,4 |
| K- 07 40 25 43 | 4 mm | 33,4 | 16,7 |
| K- 07 40 25 44 | 5 mm | 38,4 | 19,2 |
| K- 07 40 25 45 | 6 mm | 38,0 | 19,0 |
| K- 07 40 25 46 | 8 mm | 42,6 | 21,3 |
| K- 07 40 25 47 | 10 mm | 46,6 | 23,3 |
| K- 07 40 25 48 | 12 mm | 52,0 | 26,0 |
| K- 07 40 25 49 | 14 mm | 58,6 | 29,3 |