

K-L-MEHRFACHVERT 3 DR AGR-K

Multiple union elbows with inner hex, 3 outlets, swivel type, conical male thread, coated

HANSA FLEX

Eigenschappen

| | |
|--------------------|--|
| Werkdruk | Max. 15 bar, coarse vacuum |
| Toepassingsgebied | Air, vacuum |
| aanbevolen slangen | PU or PA (nylon) |
| Middelen | Compressed air and all gases or liquids that are compatible with the materials |
| Temperatuurgebied | -20 °C to +80 °C |
| Dichtvlak | Conical version: thread coating |
| Materiaal | Plastic, Nickel plated brass |
| Aandrukring | Plastic |



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Artikel

| Aanduiding | Schroefdraad | voor uitw. slang-Ø | Binnenzeskant (mm) | L1 (mm) | L2 (mm) | SW |
|----------------|--------------|--------------------|--------------------|---------|---------|-------|
| K- 07 40 05 31 | R 1/8 | 4 mm | 4,0 | 59,6 | 22,5 | 14 mm |
| K- 07 40 05 32 | R 1/8 | 6 mm | 4,0 | 59,6 | 21,5 | 14 mm |
| K- 07 40 05 33 | R 1/8 | 8 mm | 4,0 | 59,6 | 24,5 | 14 mm |
| K- 07 40 05 29 | R 1/4 | 6 mm | 6,0 | 81,0 | 23,5 | 17 mm |
| K- 07 40 05 30 | R 1/4 | 8 mm | 6,0 | 81,0 | 26,5 | 17 mm |
| K- 07 40 05 27 | R 1/4 | 10 mm | 6,0 | 81,0 | 29,9 | 17 mm |
| K- 07 40 05 28 | R 1/4 | 12 mm | 6,0 | 81,0 | 30,8 | 17 mm |
| K- 07 40 05 36 | R 3/8 | 8 mm | 8,0 | 83,7 | 28,5 | 20 mm |
| K- 07 40 05 34 | R 3/8 | 10 mm | 8,0 | 83,7 | 31,9 | 20 mm |
| K- 07 40 05 35 | R 3/8 | 12 mm | 8,0 | 83,7 | 32,8 | 20 mm |