

K-L-STECK VB

Union elbows

HANSA FLEX

Eigenschappen

| | |
|---------------------|---------------------|
| Werkdruk | Max. 16 bar |
| Bedrijfstemperatuur | -20 °C to +150 °C |
| Materiaal | messing vernikkeld |
| Aandrukkring | Nickel-plated brass |
| Spanring | Stainless steel |



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

Artikel

| Aanduiding | voor uitw. slang-Ø | L1 (mm) | L2 (mm) |
|----------------|--------------------|------------|------------|
| K- 07 40 27 53 | 4 mm | 17,5 | 17,5 |
| K- 07 40 27 54 | 6 mm | 20,0 | 20,0 |
| K- 07 40 27 55 | 8 mm | 23,0 | 23,0 |
| K- 07 40 27 56 | 10 mm | 25,0 | 25,0 |
| K- 07 40 47 79 | 12 mm | 27,5 | 27,5 |
| K- 07 40 47 80 | 14 mm | 31,0 | 31,0 |