


TR HL

Inslagnippel, CEL

Eigenschappen

| | |
|-----------------------------|-----------------------------------|
| Aansluiting 1 | Metrische buitendraad cilindrisch |
| Afdichtingsvorm 1 | 24° binnenconus |
| Norm | ISO 8434-1 |
| Materiaal | Staal |
| Oppervlakbescherming | Galvanisch gecoat |



Artikel

| Aanduiding | DN | Size | Duim | voor uitw. buis-Ø (mm) | G1 | L1 (mm) |
|-------------|----|------|-------|---------------------------|------------|------------|
| TR 04 HL | 5 | 3 | 3/16" | 6 | M 12 x 1,5 | 30 |
| TR 06 HL | 6 | 4 | 1/4" | 8 | M 14 x 1,5 | 31 |
| TR 08 HL 06 | 8 | 5 | 5/16" | 8 | M 14 x 1,5 | 38 |
| TR 08 HL | 8 | 5 | 5/16" | 10 | M 16 x 1,5 | 38 |
| TR 10 HL 08 | 10 | 6 | 3/8" | 10 | M 16 x 1,5 | 38 |
| TR 10 HL | 10 | 6 | 3/8" | 12 | M 18 x 1,5 | 39 |
| TR 13 HL | 12 | 8 | 1/2" | 15 | M 22 x 1,5 | 52 |