


K-DRG MANO HANSA PRO

Pressure regulator, with pressure gauge, HANSA PRO

HANSA FLEX

Eigenschappen

| | |
|--------------------------------|---|
| Uitgangsdruk | Pa 0,5 - 8 bar (Standart)Pa 0,1 - 1 barPa 0,1 - 2 barPa 0,2 - 4 barPa 0,5 - 10 barPa 0,5 - 16 bar |
| Mediumtemperatuur | -10 °C to +50 °C |
| Omgevingstemperatuur | -10 °C to +50 °C |
| Middelen | Perslucht |
| Constructie | Diaphragm pressure regulator with relieving |
| Bevestigingsmethode | Line mounting, panel mounting, mounting kit or wall mounting |
| Bediening / beveiliging | lockable handwheel |
| Inbouwpositie | Any |
| Manometeraansluiting | G 1/4 i |
| Nominaal debiet G 1/2 | 5.100 l/min (P1 = 10 bar, P2 = 6,3 bar/Delta P = 1 bar) |
| Nominaal debiet G 3/8 | 4.300 l/min (P1 = 10 bar, P2 = 6,3 bar/Delta P = 1 bar) |
| Pe max | 16 bar |
| Behuizing | PA66 |
| Membranen, afdichtingen | Ms/NBR/PA6 |



Artikel

| Aanduiding | Aansluiting | Regelbereik | Weergavebereiken | Maat |
|----------------|-------------|--------------|------------------|------|
| K- 07 25 21 36 | G 3/8 i | 0.1 - 1 bar | 0 - 1,6 bar | 2 |
| K- 07 25 21 37 | G 3/8 i | 0.1 - 2 bar | 0 - 2,5 bar | 2 |
| K- 07 25 21 38 | G 3/8 i | 0.2 - 4 bar | 0 - 6 bar | 2 |
| K- 07 25 21 39 | G 3/8 i | 0.5 - 8 bar | 0 - 10 bar | 2 |
| K- 07 25 21 40 | G 3/8 i | 0.5 - 10 bar | 0 - 16 bar | 2 |
| K- 07 25 21 41 | G 3/8 i | 0.5 - 16 bar | 0 - 25 bar | 2 |
| K- 07 25 21 42 | G 1/2 i | 0.1 - 1 bar | 0 - 1,6 bar | 2 |
| K- 07 25 21 43 | G 1/2 i | 0.1 - 2 bar | 0 - 2,5 bar | 2 |
| K- 07 25 21 44 | G 1/2 i | 0.2 - 4 bar | 0 - 6 bar | 2 |
| K- 07 25 21 45 | G 1/2 i | 0.5 - 8 bar | 0 - 10 bar | 2 |
| K- 07 25 21 46 | G 1/2 i | 0.5 - 10 bar | 0 - 16 bar | 2 |
| K- 07 25 21 47 | G 1/2 i | 0.5 - 16 bar | 0 - 25 bar | 2 |